



QUALITY MANAGEMENT
SYSTEM
CERTIFIED ISO 9001

TECHNICAL DATA SHEET

Series

30811

DISTACCANTE SI-3

- **SUMMARY** **RELEASING AGENT FOR MOULDS, WHEN PRODUCING ITEMS MADE OF POLYESTER AND POLYETHER PU, MELAMINIC, PHENOLIC, POLYESTER AND EPOXY RESINS, COLD MOULDS PVC**
- **DESCRIPTION** Ready-blend releasing agent into not hazardous solvents. It doesn't contain methylen-chloride. **DISTACCANTE SI-3 30811** is excellent when moulding polyurethane foams, rigid or semirigid. Particularly hard to be taken off. Whether these items have also to be glued or varnished, it's imperative to degrease them.
- **CHARACTERISTICS**
 - Look clear liquid
 - Colour colourless
 - Content in active substances in % 5 approx.
 - Flammability class 3
- **APPLICATION**
 - To be applied by a small brush, pad or by a spray-gun
 - avoid long contact with the skin
 - in case it's sprayed into eyes, wash with a generous quantity of water
 - it's imperative to apply the product onto perfectly clean and degreased moulds
 - application of **DISTACCANTE SI-3 30811** may vary according to the size of injected items and to the used material as standard
 - one application allows the extraction of 2 - 10 mouldings
- **COLOURS** Colourless
- **SOLVENTS** It doesn't necessary
- **PACKING** Drum of Lt. 200
- **STORAGE** Shelf life: about 24 months if stored in well closed original packings in a dry and airy place.
Temperature: from 5°C. to 35°C.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

15-05-07 RM/pm