



QUALITY MANAGEMENT
SYSTEM
CERTIFIED ISO 9001

TECHNICAL DATA SHEET

ECOSAR 15

● SUMMARY SYNTHETIC LATEX, ADHESIVE IN WATERY DISPERSION

● **USE** Particularly suitable for small leather-goods (wallets), for leather and synthetic cementing. Application by spraying system.

● **CHARACTERISTICS**

– Appearance	white liquid
– Viscosity	450 +/- 50 cps (G3 – V20)
– pH value	between 8 and 9
– Dry content	51,5 +/- 5

● **APPLICATION**

- **ECOSAR 15** has to be applied onto one sole side, leather or synthetic
- after 5 - 10 minutes join nylon or silk and press (process valid for small leather-goods)
- thanks to its high stickness, it can be used for other works demanding the application onto both parts (bags, etc.)

Notes: it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

● **STORAGE**

The expire date of the product shown on the label is valid for products if kept away from direct heat and cold and at standard storage conditions (minimum temperature 4°C to maximum 40°C). Exceeding the expiration date does not necessarily mean that the product no longer meets the specifications or values set. However, before using this product after the expiration date, Kenda Farben recommends checking whether it still meets the reference specifications or values. Kenda Farben will not be in any way responsible for failure to comply with specifications or values set after the deadline or due to incorrect storage that can shorten the life of the product.

● **NOTE**

Stir it well before its use. Keep from freezing.
Keep the packings perfectly closed.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

30-09-2021 GA/pm