



TECHNICAL DATA SHEET

Series

16

SAR 534

• SUMMARY

ADHESIVE FOR FURNITURE AT TR RUBBER BASE SUITABLE FOR BONDING OF EXPANDED RUBBERS - VERY GOOD RESISTANCE TO HEAT

• CHARACTERISTICS

Adhesive

monocomponent at TR rubber base

transparent light yellow

Colour SAR 534Colour SAR 534 R

Viscosity Ford cup n. 4 at 20°C

80" +/- 5"

red

Open timeSpecific weight at 20°C

7 minutes 0.84 +/- 0.01

Solid content

35 +/- 1%

Solvents content according to current law regulations

- Flammable

• APPLICATION

- Apply the adhesive by spraying-gun with nozzle from 1.6 to 2.5 mm, then join the adhesived parts
- it is possible to bond the 2 surfaces putting a slight pressure after 2 minutes from spraying

<u>Notes</u>: it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

• SOLVENTS

Use **SOLVENTE 31708** for spraying gun cleaning

• PACKING

Tin of Kg. 14 n.w.

• STORAGE

Shelf life: about 12 months if stored in well closed tins at 15 - 25°C.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.