



## TECHNICAL DATA SHEET

Series

16

**SAR 535**

### ● SUMMARY

**ADHESIVE FOR FURNITURE AT TR RUBBER BASE SUITABLE FOR  
BONDING OF EXPANDED RUBBERS - VERY GOOD RESISTANCE TO HEAT**

### ● CHARACTERISTICS

- Adhesive monocomponent at TR rubber base
- Colour **SAR 535** transparent light yellow
- Viscosity Ford cup n. 4 at 20°C 105'' +/- 5''
- Open time 7 minutes
- Specific weight at 20°C 0,87 +/- 0,1
- Solid content 40 +/- 1%
- Solvents content according to current law regulations
- Flammable

### ● APPLICATION

- Apply the adhesive by spraying-gun with nozzle from 1.6 to 2.5 mm, then join the adhesived parts
- it is possible to bond the 2 surfaces putting a slight pressure after 2 minutes from spraying

**Notes:** it is suggested to use the adhesive at temperatures not lower than 18°; in case the material is stocked in cold ambients, recondition before using

### ● SOLVENTS

Use **SOLVENTE 31700** for spraying gun cleaning

### ● PACKING

Tin of Kg. 14 n.w.

### ● STORAGE

Shelf life: about 12 months if stored in well closed tins at 15 - 25°C.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

27-06-2019 RM/pm