



TECHNICAL DATA SHEET

Series

92

TERMOLAC

● **SUMMARY** **FIXING VARNISH WITH SPECIAL FINISH SOLES BOTTOM, PAINTED WITH TERMOLUX**

● **DESCRIPTION** **TERMOLAC** is a special varnish for painting and fixing the soles bottom and thermoplastic rubber items painted with **TERMOLUX**.
The main application of **TERMOLAC** allows to obtain leather effect onto thermoplastic items (covering, base coat **TERMOLUX** - transparent, top coat **TERMOLAC**).
TERMOLAC is only a top coat (coloured or transparent version) after the application of **TERMOLUX** as base coat.
TERMOLAC main feature is the elasticity without being sticky, joined to a strong adhesion to the sole bottom painted with **TERMOLUX**.

● **APPLICATION** – After **TERMOLUX** as base coat, apply **TERMOLAC** as top coat by means of a spray-gun nozzle 1 - 1.2 at a pressure of 3 - 4 ATM

Note: do not apply **TERMOLAC** directly to thermoplastic items.

● **COLOURS** 39200 Colourless
39281 Brown

● **SOLVENTS** Use **SOLVENTE 31702** for thinnings and washings

● **PACKING** Can of Kg. 18

● **STORAGE** Shelf life: about 24 months if stored in well closed original packings in a dry and airy place.
Keep from freezing and extreme heat.

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

31-05-04 RM/pm