

TECHNICAL DATA SHEET

Series

89

TERMOLUX

| • SUMMARY | HIGH GLOSSY, COVERING VARNISH FOR UNHALOGENATED TR RUBBER SOLES | |
|---------------|---|--|
| • DESCRIPTION | TERMOLUX is a super-glossy and bright varnish for unhalogenated TR rubber dyeing. To be applied directly on TR rubber, being a monocomponent, ready-blend varnish, highly elastic and flexible. TERMOLUX has got an excellent adhesion power onto unhalogenated TR rubber and its glossy finish endures in the time. Due to its peculiar features TERMOLUX can be applied either manually or by spraying, getting first-class covering and brightening results. TERMOLUX is a versatile varnish which can be used itself as monochrome, as base coat for leatherette using then SPAZZOLATO (see technical data sheet series 20) or SFUMATO (see technical data sheet series 53), or as first coat for antique effects onto TR rubber using then PRODOTTO S series 81. | |
| • APPLICATION | Apply TERMOLUX by spray, manually or by means of special automatic machines produced by "MET" in Gropello Cairoli it can also be applied by means of a small brush | |
| • COLOURS | Glossy effect: 38901 Black Semi-glossy base coats for leather effects: 389301 Reddish brown 389300 Colourless 389312 Orange brown | 38900 Colourless 389302 Beige 389304 Black |
| • SOLVENTS | Use SOLVENTE 31702 for thinnings and washings | |
| • PACKING | Drum of Kg. 20 | |
| • STORAGE | Shelf life: about 24 months if stored in well closed original packings in a dry and airy place. Keep from freezing and extreme heat. | |

This information is to the best of our knowledge true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

30-05-2019 RM/pm